

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Opteon™ XL55 (R-452B) Refrigerant  
SDS-Identcode : 130000143544

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Refrigerant  
Recommended restrictions on use : For professional and industrial installation and use only., Do not use product for anything outside of the above specified uses

#### 1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.  
Baanhoekweg 22  
3313 LA Dordrecht Netherlands  
Telephone : +31-(0)-78-630-1011  
Telefax : +31-78-6163737  
E-mail address of person responsible for the SDS : sds-support@chemours.com

#### 1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1      H220: Extremely flammable gas.  
Gases under pressure, Liquefied gas      H280: Contains gas under pressure; may explode if heated.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

Signal word : Danger

Hazard statements : H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**Response:**  
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 In case of leakage, eliminate all ignition sources.  
**Storage:**  
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

### Additional Labelling

Contains fluorinated greenhouse gases. (HFC-32, HFC-125)

### 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

May displace oxygen and cause rapid suffocation.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Difluoromethane*	75-10-5 200-839-4 01-2119471312-47	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	67
2,3,3,3-Tetrafluoropropene*	754-12-1 468-710-7 01-0000019665-61	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	26
Pentafluoroethane*	354-33-6 206-557-8 01-2119485636-25	Press. Gas Liquefied gas; H280	7

\* Voluntarily-disclosed non-hazardous substance

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

For explanation of abbreviations see section 16.

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                            |   |  |
|----------------------------|---|--|
| General advice             | : | In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice. |
| Protection of first-aiders | : | No special precautions are necessary for first aid responders.   |
| If inhaled                 | : | If inhaled, remove to fresh air.<br>Get medical attention if symptoms occur.   |
| In case of skin contact    | : | Thaw frosted parts with lukewarm water. Do not rub affected area.<br>Get medical attention immediately.  |
| In case of eye contact     | : | Get medical attention immediately.   |
| If swallowed               | : | Ingestion is not considered a potential route of exposure.   |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |  |
|----------|---|--|
| Symptoms | : | May cause cardiac arrhythmia.<br><br>Other symptoms potentially related to misuse or inhalation abuse are<br>Cardiac sensitisation<br>Anaesthetic effects<br>Light-headedness<br>Dizziness<br>confusion<br>Lack of coordination<br>Drowsiness<br>Unconsciousness |
| Risks    | : | Contact with liquid or refrigerated gas can cause cold burns and frostbite.  |

#### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |   |
|-----------|---|---|
| Treatment | : | Treat symptomatically and supportively. |
|-----------|---|---|
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- |                              |   |  |
|------------------------------|---|--|
| Suitable extinguishing media | : | Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> ) |
|------------------------------|---|--|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Vapours may form flammable mixture with air  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
Carbon oxides  
Fluorine compounds

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Only trained personnel should re-enter the area.  
Remove all sources of ignition.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.  
Non-sparking tools should be used.  
Suppress (knock down) gases/vapours/mists with a water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

spray jet.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |   |  |
|-------------------------|---|--|
| Technical measures      | : | Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.  |
| Local/Total ventilation | : | Use with local exhaust ventilation.<br>Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential  |
| Advice on safe handling | : | Avoid breathing gas.<br>Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.<br>Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.<br>Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.<br>Never attempt to lift cylinder by its cap.<br>Do not drag, slide or roll cylinders.<br>Use a suitable hand truck for cylinder movement.<br><br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Keep container tightly closed.<br>Wear cold insulating gloves/ face shield/ eye protection.<br>Prevent backflow into the gas tank.<br>Open the valves slowly to prevent pressure surges.<br>Close valve after each use and when empty. Do NOT change or force fit connections.<br>Prevent the intrusion of water into the gas tank.<br>Keep away from heat and sources of ignition.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures        | : | Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Acutely toxic substances and mixtures  
Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage temperature : < 52 °C

Further information on storage stability : The product has an indefinite shelf life when stored properly.

### 7.3 Specific end use(s)

Specific use(s) : No data available

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Difluoromethane	Workers	Inhalation	Long-term systemic effects	7035 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	750 mg/m <sup>3</sup>
2,3,3,3-Tetrafluoropropene	Workers	Inhalation	Long-term systemic effects	950 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

Pentafluoroethane	Workers	Inhalation	Long-term systemic effects	16444 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	1753 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Difluoromethane	Fresh water	0.142 mg/l
	Intermittent use/release	1.42 mg/l
	Fresh water sediment	0.534 mg/kg
2,3,3,3-Tetrafluoropropene	Fresh water	0.1 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	1.77 mg/kg dry weight (d.w.)
	Soil	1.54 mg/kg dry weight (d.w.)
Pentafluoroethane	Marine water	0.01 mg/l
	Marine sediment	0.178 mg/kg dry weight (d.w.)
	Fresh water	0.1 mg/l
Pentafluoroethane	Intermittent use/release	1 mg/l
	Fresh water sediment	0.6 mg/kg

## 8.2 Exposure controls

### Engineering measures

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

Use with local exhaust ventilation.

### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
Face-shield

Hand protection  
Material : Heat resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

- Skin and body protection : Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic gas and low boiling vapour type (AX)
- Protective measures : Wear cold insulating gloves/ face shield/ eye protection.
- 

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- Appearance : Liquefied gas
- Colour : clear, colourless
- Odour : slight, ether-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : -51 °C
- Flash point : Not applicable
- Evaporation rate : > 1  
(CCL4=1.0)
- Flammability (solid, gas) : Flammable
- Upper explosion limit / Upper flammability limit : Upper flammability limit  
23.3 %(V)  
Method: ASTM E681
- Lower explosion limit / Lower flammability limit : Lower flammability limit  
12 %(V)  
Method: ASTM E681
- Vapour pressure : 15,987 hPa (25 °C)
- Relative vapour density : No data available
- Relative density : 0.99 (25 °C)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

Density	:	0.99 g/cm <sup>3</sup> (25 °C)
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Particle size	:	Not applicable
---------------	---	----------------

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Vapours may form flammable mixture with air Can react with strong oxidizing agents. Extremely flammable gas.
---------------------	---	--

### 10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

### 10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

### Components:

#### **Difluoromethane:**

Species: Not tested on animals  
Result: No skin irritation

#### **2,3,3,3-Tetrafluoropropene:**

Species: Not tested on animals  
Result: No skin irritation

#### **Serious eye damage/eye irritation**

Not classified based on available information.

### Components:

#### **Difluoromethane:**

Species: Not tested on animals  
Result: No eye irritation

#### **2,3,3,3-Tetrafluoropropene:**

Species: Not tested on animals  
Result: No eye irritation

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

Not classified based on available information.

##### **Respiratory sensitisation**

Not classified based on available information.

### Components:

#### **Difluoromethane:**

Exposure routes: Skin contact  
Species: Not tested on animals  
Result: negative

Species: Not tested on animals  
Result: negative

#### **2,3,3,3-Tetrafluoropropene:**

Exposure routes: Skin contact  
Species: Not tested on animals  
Result: negative

#### **Germ cell mutagenicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

### Components:

#### **Difluoromethane:**

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

#### **2,3,3,3-Tetrafluoropropene:**

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

#### **Pentafluoroethane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### Components:

#### **2,3,3,3-Tetrafluoropropene:**

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **Difluoromethane:**

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials

#### **2,3,3,3-Tetrafluoropropene:**

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

#### **Pentafluoroethane:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 414  
Result: negative

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Components:

#### Difluoromethane:

Assessment: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

#### 2,3,3,3-Tetrafluoropropene:

Assessment: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Repeated dose toxicity

### Components:

#### Difluoromethane:

Species: Rat  
NOAEL: 49100 ppm  
Application Route: inhalation (gas)  
Exposure time: 90 d  
Remarks: No significant adverse effects were reported

#### 2,3,3,3-Tetrafluoropropene:

Species: Rat  
NOAEL: 50000 ppm  
LOAEL: >50000 ppm  
Application Route: inhalation (gas)  
Exposure time: 90 d  
Method: OECD Test Guideline 413  
Remarks: No significant adverse effects were reported

#### Pentafluoroethane:

Species: Rat  
NOAEL: >= 50000 ppm  
Application Route: inhalation (gas)  
Exposure time: 13 Weeks  
Method: OECD Test Guideline 413

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **Difluoromethane:**

- Toxicity to fish : LC50 (Fish): 1,507 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 652 mg/l  
Exposure time: 48 h
- Toxicity to algae : EC50 (algae): 142 mg/l  
Exposure time: 96 h
- Toxicity to fish (Chronic toxicity) : NOEC: 65.8 mg/l  
Exposure time: 30 d  
Species: Fish

##### **2,3,3,3-Tetrafluoropropene:**

- Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 197 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h
- Toxicity to algae : NOEC (algae): > 100 mg/l  
Exposure time: 72 h

##### **Pentafluoroethane:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l  
Exposure time: 96 h  
Method: Directive 67/548/EEC, Annex V, C.1.  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 980 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.  
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 114 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### 12.2 Persistence and degradability

#### Components:

##### **Difluoromethane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **2,3,3,3-Tetrafluoropropene:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301F

##### **Pentafluoroethane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Components:

##### **Difluoromethane:**

Partition coefficient: n-octanol/water : log Pow: 0.714

##### **2,3,3,3-Tetrafluoropropene:**

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

##### **Pentafluoroethane:**

Partition coefficient: n-octanol/water : Pow: 1.48 (25 °C)

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB)..

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

### 12.6 Other adverse effects

#### Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

#### Product:

100-year global warming potential: 698.29

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty pressure vessels should be returned to the supplier.  
If not otherwise specified: Dispose of as unused product.
- 

## SECTION 14: Transport information

### 14.1 UN number

- ADN : UN 3161  
ADR : UN 3161  
RID : UN 3161  
IMDG : UN 3161  
IATA (Cargo) : UN 3161  
IATA (Passenger) : UN 3161  
Not permitted for transport

### 14.2 UN proper shipping name

- ADN : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
ADR : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
RID : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
IMDG : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
IATA (Cargo) : Liquefied gas, flammable, n.o.s.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)
-



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

**IATA (Passenger)** : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
Not permitted for transport

### 14.3 Transport hazard class(es)

**ADN** : 2  
**ADR** : 2  
**RID** : 2  
**IMDG** : 2.1  
**IATA (Cargo)** : 2.1  
**IATA (Passenger)** : Not permitted for transport

### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 2F  
Hazard Identification Number : 23  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 2F  
Hazard Identification Number : 23  
Labels : 2.1  
Tunnel restriction code : (B/D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 2F  
Hazard Identification Number : 23  
Labels : 2.1 ((13))

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 200  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)** : Not permitted for transport

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : no

**ADR**  
Environmentally hazardous : no

**RID**  
Environmentally hazardous : no

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version 3.3      Revision Date: 13.12.2017      SDS Number: 1354803-00034      Date of last issue: 20.11.2017  
Date of first issue: 27.02.2017

---

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P2	FLAMMABLE GASES	Quantity 1 10 t	Quantity 2 50 t
----	-----------------	--------------------	--------------------

#### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

---

## SECTION 16: Other information

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

### Full text of H-Statements

H220 : Extremely flammable gas.  
H280 : Contains gas under pressure; may explode if heated.

### Full text of other abbreviations

Flam. Gas : Flammable gases  
Press. Gas : Gases under pressure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Flam. Gas 1 H220  
Press. Gas Liquefied gas H280

### Classification procedure:

Based on product data or assessment  
Based on product data or assessment

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL55 (R-452B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2017
3.3	13.12.2017	1354803-00034	Date of first issue: 27.02.2017

---

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN