

Printing date 23.03.2023 Version number 2 Revision: 23.03.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: R-410A

Article number: R410A STD

1.2 Relevant identified uses of the substance or mixture and uses advised against: Refrigerant

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

OSAKA UMEDA TWIN TOWERS SOUTH, 1-13-1 Umeda, Kita-ku, Osaka-shi, Osaka, 530-0001, Japan

Phone: +81-6-6147-9702 Fax: +81-6-6147-9807

Further information obtainable from: http://www.daikin.com/

1.4 Emergency telephone number:

Japan: +81-6-6349-7521

China: +86-532-8388-9090, +86-21-34151689

South Korea: +82-2-568-1722

Americas: CHEMTREC +1-800-424-9300 (Outside US/Canada: +1-703-527-3887)

Europe: +49-211-179 225-0

### SECTION 2: Hazard identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Press. Gas (Liq.) H280 Contains gas under pressure; may explode if heated.

#### 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Signal word: Warning Precautionary statements:

P410+P403 Protect from sunlight. Store in a well-ventilated place.

# SECTION 3: Composition/information on ingredients

#### Information on ingredients:

CAS: 354-33-6 Pentafluoroethane

49.5-51.5%

Press. Gas (Liq.), H280

CAS: 75-10-5 Difluoromethane

48.5-50.5%

Flam. Gas 1B, H221 Press. Gas (Liq.), H280

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

## 4.1 Description of first aid measures

General information: Seek immediate medical advice.

#### After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult a doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

In case of emergency to rescue the victims; be sure to wear supplied-air respirator (SAR) or self-contained breathing apapratus (SCBA).

If the patient does not breathe or hardly breathes, unbutton clothes, secure the airway for breathing and perform artificial respiration.

At high levels, cardiac arrhythmia may occur.

### After skin contact:

Rinse with warm water.



Printing date 23.03.2023 Version number 2 Revision: 23.03.2023

Trade name: R-410A

In cases of frost bites, rinse with plenty of water. Do not remove clothing.

Immediately rinse with warm water and soap.

Consult a doctor in case of complaints.

#### After eye contact:

Rinse opened eye for several minutes under running water.

Consult an ophthalmologist in case of complaints.

After swallowing: Not applicable.

### Information for doctor:

Catecholamines such as adrenaline, and other compounds having similar effects, should be reserved for emergencies and then used only with special caution.

The examining physician should advise workers taking medications containing catecholamines that they may be at increased risk and should avoid excessive exposure.

#### 4.2 Most important symptoms and effects, both acute and chronic:

Frost bites

High concentrations cause asphyxiation. May cause an abnormal heart rhythm and prove suddenly fatal.

### 4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

# SECTION 5: Firefighting measures

## 5.1 Extinguishing media

# Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable for surrounding conditions.

### 5.2 Special hazards arising from the substance or mixture:

Hydrogen fluoride (HF)

Formation of toxic gases is possible during heating or in case of fire.

Receptacle may explode when heated.

# 5.3 Advice for firefighters:

Move receptacle to a safe place immediately if possible. If not, spray water on the receptacles and surrounding equipment to cool.

If receptacle catches fire: cool them with plenty of water.

If possible, close valves of receptacles to shut off the gas supply.

### Protective equipment:

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

## SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Remove persons from danger area.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not inhale the product.

Ensure adequate ventilation before entering the area.

Stay on the windward side.

Keep out unauthorized persons.

## 6.2 Environmental precautions:

Suppress gases/fumes/haze with water spray.

Do not allow to enter sewers/surface or ground water.

Must not be emitted into the environment.

### **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.

# 6.4 Reference to other sections:

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

# 7.1 Precautions for safe handling:

Waste air is to be released into the atmosphere only via suitable separators.



Printing date 23.03.2023 Version number 2 Revision: 23.03.2023

Trade name: R-410A

Ensure good ventilation/exhaustion at the workplace.

Handle with care. Avoid jolting, friction and impact.

For heating receptacle, use hot compresses or lukewarm water below 40  $^{\circ}$ C.

Do not use heaters.

Stay on the windward side when working outdoors.

Be careful of leakage when attaching/detaching receptacles.

Inhaling large quantities may cause cardiac arrhythmia or asphyxiation or both.

Keep away from naked flame or metal heated over 300 - 400  $^{\circ}$ C to prevent thermal decomposition that may form toxic gases.

Do not handle until all safety precautions have been read and understood.

## Information about fire - and explosion protection:

The product is not flammable.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

#### 7.2 Conditions for safe storage, including any incompatibilities:

#### Storage

#### Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Store in a cool and dry location.

Keep containers tightly sealed.

### Information about storage in one common storage facility:

See section 10 for information on incompatible materials.

### Further information about storage conditions:

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

7.3 Specific end use(s): No further relevant information available.

### SECTION 8: Exposure controls/personal protection

## **8.1 Control parameters** No further information available.

### Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

#### 8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Do not smoke.

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

Respiratory protection: Use respiratory protective device with organic gas cartridge.

## Hand protection



To avoid skin problems reduce the wearing of gloves to the required minimum.

#### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Leather



Printing date 23.03.2023 Version number 2 Revision: 23.03.2023

Trade name: R-410A

#### Eye/face protection



Body protection: Protective work clothing

# SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Physical stateLiquefied gasColour:ColourlessOdour:Ether-likeOdour threshold:Not determined.Melting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range-52.7 °CFlammabilityNo data.

Lower and upper explosion limit

Lower explosive limit: No further information available.

Upper explosive limit:Not determined.Flash point:Not applicable.

**Decomposition temperature:** No further information available.

pH Not applicable.

Viscosity:

Kinematic viscosity

Dynamic:

Not determined.

Not determined.

Solubility

water:No further information available.Partition coefficient n-octanol/water (log value)No further information available.Vapour pressure at 25 °C:1.65 MPa (16,84 kgf/cm2 abs)

Density and/or relative density

Density at 25 °C: 1.06 g/cm³
Relative density at 25 °C 1.06

**Vapour density at 25 °C** 0.056 (/100g H2O 1atm)

**Particle characteristics**No further information available.

9.2 Other information:

Form: Liquefied gas

Auto-ignition temperature: Product is not self-igniting.

Explosive properties:Not determined.Evaporation rateNot applicable.

Information with regard to physical hazard classes

ExplosivesNot applicableFlammable gasesNot applicableAerosolsNot applicableOxidising gasesNot applicable

Gases under pressure

Contains gas under pressure; may explode if heated.

Flammable liquids
Flammable solids
Not applicable
Self-reactive substances and mixtures
Not applicable
Pyrophoric liquids
Pyrophoric solids
Not applicable
Self-heating substances and mixtures
Not applicable
Not applicable

Substances and mixtures, which emit flammable gases

in contact with waterNot applicableOxidising liquidsNot applicable



Printing date 23.03.2023 Version number 2 Revision: 23.03.2023

Trade name: R-410A

Oxidising solidsNot applicableOrganic peroxidesNot applicableCorrosive to metalsNot applicableDesensitised explosivesNot applicable

## SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: Alkali or alkaline earth metals - powdered Al, Zn, Mg, etc.

10.6 Hazardous decomposition products: Hydrofluoric acid, carbonyl fluoride

# SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 No futher information available.

Acute toxicity no data

LD/LC50 values relevant for classification: No further information available.

Skin corrosion/irritation: No further information available. Serious eye damage/irritation: No further information available.

after inhalation: No further information available.

**Respiratory or skin sensitisation:** No further information available.

Germ cell mutagenicity:

In vitro tests did not show mutangenic effects. (Pentafluoroethane) In vivo tests did not snow mutangenic effects. (Pentafluoroethane)

Carcinogenicity: No further information available.

Reproductive toxicity:

*No toxicity to reproduction (Pentafluoroethane)* 

Inhalation, mouse, 208000 mg/m3, Effect on fertility, NOAEC (Difluoromethane)

foetotoxic effect (Difluoromethane)

STOT-single exposure: No further information available.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard:

Other information (about experimental toxicology): No further information available.

Subacute to chronic toxicity: No further information available.

11.2 Information on other hazards: Endocrine disrupting properties:

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

Abiotic degradation:

Air, indirect photo-oxidation, t 1/2 from 4.16-28.2 y

Conditions: sensitizer: OH radicals

Degradation products: Carbon dioxide (CO2)/hydrofluoric acid/ TFA

12.3 Bioaccumulative potential:

Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment

**PBT:** No further relevant information available.

vPvB: No further information available.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects: Ecotoxical effects: no data



Printing date 23.03.2023 Version number 2 Revision: 23.03.2023

Trade name: R-410A

#### Additional ecological information:

General notes:

Ozone depletion potential(ODP): 0(CFC-11 1.0)

Global warming potential(GWP): 1700(CO2=1 100years integrated value)

# SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Recommendation:

Disposal must be made according to official regulations. Incineration in an adequate incinerator is recommended.

Uncleaned packaging

**Recommendation:** Disposal must be made according to official regulations.

# SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1078

14.2 UN proper shipping name:

ADR, IMDG, IATA REFRIGERANT GAS, N.O.S.

14.3 Transport hazard class(es):

ADR



Class: 2 Gases. Label: 2.2 IMDG, IATA



 Class:
 2.2 Gases.

 Label:
 2.2

14.4 Packing group:

ADR: Not applicable

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user: Warning: Gases.

Hazard identification number (Kemler code): 20
Stowage Category A
14.7 Maritime transport in bulk according to IMO

*instruments* Not applicable.

Transport/Additional information: Avoid direct sunlight. Make sure of no damage, corrosion, leaks

on the receptacles.

Take necessary measures for preventing cargo shift.

ADR

Limited quantities (LQ): 120 ml Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Tunnel restriction code:

*IMDG* 

Limited quantities (LQ) 120 ml



Printing date 23.03.2023 Version number 2 Revision: 23.03.2023

Trade name: R-410A

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1078 REFRIGERANT GAS, N.O.S., 2.2

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Warning

Hazard statements

H280 Contains gas under pressure; may explode if heated.

Precautionary statements

P410+P403 Protect from sunlight. Store in a well-ventilated place.

National regulations No further information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** EHS Department

Contact: http://www.daikin.com/ Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1B: Flammable gases - Category 1B

Press. Gas (Liq.): Gases under pressure - Liquefied gas

<sup>\*</sup> Data compared to the previous version altered.